

## DATA SHEET - CHAIN SLINGS



Code	Capacity (kg)	Length (mm)	Diametre (mm)
C10.1.500ZSL	3150	500	10
C10.1.1000ZSL	3150	1000	10
C13.1.1000ZSL	5300	1000	13
C16.1.1000NSL	8000	1000	16
C20.1.1000NSL	12500	1000	20
C07.2.2000ZGC	2100	2000	7
C08.2.2000ZGC	2800	2000	8
C10.2.2000ZGC	4400	2000	10
C13.2.2000ZGC	7500	2000	13
C07.3.2000ZGC	3150	2000	7
C08.3.2000ZGC	4200	2000	8
C10.3.2000ZGC	6600	2000	10
C07.4.1500ZGC	3150	1500	7
C07.4.3000ZGC	3150	3000	7
C10.4.2000ZGC	6700	2000	10



## DATA SHEET - CHAIN SLINGS

Code	Capacity (kg)	Length (mm)	Diametre (mm)
C13.4.2000ZGC	11200	2000	13



## DATA SHEET - CHAIN SLINGS

---

Chain slings and straps for lifting



## Chain slings

### Assortment of chain slings

Explore our wide range of zinc-plated chain slings, designed in flexible configurations with options for **1, 2, 3, and 4 arms**, available in various lengths and load capacities. This versatile selection is designed to meet a broad range of industrial needs and applications, ensuring flexibility and adaptability in every operational context.

Our chain slings are constructed with a **safety factor of 1:4**, ensuring excellent strength and durability characteristics. These devices provide secure and reliable suspension for heavy and varied loads. Our range includes models with multiple arms, different types of hooks, and shorteners, ideal for lifting loads with multiple attachment points or unbalanced centers of gravity.

All our chain slings strictly comply with international standards, including EN 1492-1, EN 1492-2, Decree 459 of 06-09-96, CEE Machine Directive 91/368, and ISO 4878-81, ensuring the highest safety and quality standards.

For specific needs or customization requests, please feel free to contact us. Our team is available to provide assistance and tailor-made solutions that perfectly meet your requirements.

### Application sectors

 Lifting